



OR-I8 -TX8/OR22-TX8

Industrial Dye Sublimation Printer (With 8 Heads)




ORIC serisi Dijital baskı makineleri, işletmenizin ihtiyacı olan en yüksek teknolojiyi kullanır. Hem Süblimasyon hemde dogrudan tekstile baskı yapabilen yüksek kaliteli, güvenilir ve hassas yapısı ile işletmenizi rakiplerinden ayıracak kalitede baskıları garanti eder. Yüksek renk performansı ve mükemmel detaylı baskısını, alışılmamış baskı hızı ile birleştirir. Kalitenizi yarına güvenle taşır.

- Daha dayanıklı ve kararlı bir baskı için; Orijinal Epson i3200 yazıcı kafası,
- Daha düzgün kağıt besleme için; keçe silindir.
- Daha yüksek verimlilik ve yüksek performans için; 8 adet kafa yapılandırması,
- Daha doğru baskı sonucunun garantisi ve profesyonel Renk yönetimi için; Orijinal Ergosoft Texprint RIP yazılımı,
- Daha istikrarlı uzun vadeli kullanım ömrü için; Son teknoloji Endüstriyel Makine Tasarım konsepti, Güçlü gövde
- Tamamen kapalı kurutma sistemi ve sessiz fanlar sayesinde gürültüsüz performans
- Daha düşük üretim maliyeti için; Jumbo Bobin besleme sistemi



Technical Specifications

Model		OR18-TX8	OR22-TX8
Print Head		Eight I3200 Print Heads	
Printing Technology		Piezoelectric Inkjet	
Acceptable Media	Width	72 in.(1830 mm)	87.8 in.(2230 mm)
	Thickness	Maximum 39 mil(1 mm)	
	Maximum Media Load	1000m	
Printing Width		70.8 in.(1800 mm)	86.6 in.(2200 mm)
Ink Cartridges	Type	Dye Sublimation Ink	
	Capacity	4*4 CISS (220ml ink cartridge with 5L ink tank)	
	Color	4 colors (Cyan, Magenta, Yellow, Black)	
Printing Resolution		Maximum 3600 dpi	
Printing Speed		1pass(360x1200dpi): 360 sqm/h 2pass(360x2400dpi): 180 sqm/h 3pass(360x3600dpi): 100 sqm/h	1pass(360x1200dpi): 380 sqm/h 2pass(360x2400dpi): 196 sqm/h 3pass(360x3600dpi): 120 sqm/h
Media Heating System		Intergrated post heater & Infrared Dryer & Fan system	
Interface		USB 3.0	
Power Supply		AC 220V ± 10%, 50/60 HZ	
Dimensions(with stand)		133.86(W)x47.24(D)x78.74(H) in. (3400(W)x1200(D)x2000(H) mm)	149.60(W)x47.24(D)x78.74(H) in. (3800(W)x1200(D)x2000(H) mm)
Weight(with stand)		650 kg	750 kg
Package Dimensions		133.86(W)x55.12(D)x86.61(H) in. (3600(W)x1400(D)x2200(H) mm)	157.48(W)x55.12(D)x86.61(H) in. (4000(W)x1400(D)x2200(H) mm)
Package Weight		700 kg	800 kg
Environment	Power on	Temperature: 59 ℉ to 90 ℉ [15℃ to 32℃] / Humidity: 35 to 80% (no condensation)	
	Power off	Temperature: 41 ℉ to 104 ℉ [5℃ to 40℃] / Humidity: 20 to 80% (no condensation)	
Accessories		USB cable, media clamp, manual, drain bottle, ink cartridges, RIP software, etc.	



Machine cover increases cylinder control, More labor-saving and convenient .




Carriage bottom plate increases double-side heating.




Inflatable take up and feed media shaft.



Honeycomb suction platform ensure the flatness of the paper more effectively when printing .



Junbo media roll maxi 1000m media load.



Frequency motor ensures more stable material loading and take-up

ORIC Sublimation Ink



Eight I3200 Heads
CMYK



* 1.8m Eight I3200 Print Heads Speed

360x1200dpi - 1pass	360 m ² /h
360x2400dpi - 2pass	180 m ² /h
360x3600dpi - 3pass	100 m ² /h

* 2.2m Eight I3200 Print Heads Speed

360x1200dpi - 1pass	380 m ² /h
360x2400dpi - 2pass	196 m ² /h
360x3600dpi - 3pass	120 m ² /h